

Dewpoint transmitter to $-45\text{ }^{\circ}\text{C}_{\text{td}}$



SPECIFICATIONS

testo 6740


The testo 6740 was especially developed for trace humidity measurement in compressed or dry air (e. g. granulate dryers). Thanks to a special adjustment, optimum accuracy in the trace humidity range has been achieved. The result of the development of the testo 6740 is a measuring range of $-45\text{ }^{\circ}\text{C}_{\text{td}}$ to $+30\text{ }^{\circ}\text{C}_{\text{td}}$ and excellent accuracy.

For the display of the relevant trace humidity parameters, a freely scalable analog output is available, optionally with a switch contact plug for MAX monitoring. In addition to this, the testo 6740 stands out thanks to its compact and user-friendly design, such as the rotatability of the housing by 350° for the optimum positioning of the display.



SPECIFICATIONS

testo 6740

- Measurement of dewpoints in the range from $-45\text{ }^{\circ}\text{C}_{\text{td}}$ to $+30\text{ }^{\circ}\text{C}_{\text{td}}$
- Testo polymer humidity sensor with high accuracy and long-term stability
- Convenient operation via the display menu
- Analog output 4 to 20 mA (2-wire) and optional alarm plug with 2 integrated switch outputs
- Compact design with rotatable housing by 350° for optimum positioning of display
- Display with operating menu (optional)
- Trace humidity adjustment without reference measuring instrument possible on site with accessory (2-point adjustment device), replaces expensive adjustment with dewpoint mirror

Areas of application:

- Refrigeration dryers
- Membrane dryers
- Adsorption dryers
- Granulate dryers



Dewpoint transmitter to $-45\text{ }^{\circ}\text{C}_{td}$


Technical data

Measurement parameters		General technical data													
Dewpoint/trace humidity		Design													
Units	%RH, $^{\circ}\text{C}$	Material/colour	Plastic, polyacrylamide												
Calculated parameters	$^{\circ}\text{C}_{td}$, $^{\circ}\text{F}_{td}$, $^{\circ}\text{CtA}$, $^{\circ}\text{FtA}$, ppmv, mg/m^3 , $^{\circ}\text{F}$	Dimensions	199.5 x 37 x 37 mm (with standard plug) 203.5 x 37 x 37 mm (with plug 0554 3302)												
Measuring range	$-45\text{ }^{\circ}\text{C}_{td}$ to $+30\text{ }^{\circ}\text{C}_{td}$	Weight	Approx. 300 g												
Measurement uncertainty	$\pm 1\text{ K}$ at $0\text{ }^{\circ}\text{C}_{td}$ ($+32\text{ }^{\circ}\text{F}_{td}$) $\pm 3\text{ K}$ at $-20\text{ }^{\circ}\text{C}_{td}$ ($-4\text{ }^{\circ}\text{F}_{td}$) $\pm 4\text{ K}$ at $-40\text{ }^{\circ}\text{C}_{td}$ ($-40\text{ }^{\circ}\text{F}_{td}$)	Display													
Response time	$t_{90} \leq 60\text{ sec}$ for change from $13.2\text{ }^{\circ}\text{C}_{td}$ to $-32.1\text{ }^{\circ}\text{C}_{td}$ $t_{90} \leq 17\text{ sec}$ for change from $-32.2\text{ }^{\circ}\text{C}_{td}$ to $13\text{ }^{\circ}\text{C}_{td}$	Display	High intensity 7-segment display												
Sensor	Polymer humidity sensor with protocolized trace humidity adjustment at $-40\text{ }^{\circ}\text{C}_{td}$ ($-40\text{ }^{\circ}\text{F}_{td}$)	Resolution	<table border="1"> <tr> <td>$^{\circ}\text{C}$: 0.1</td> <td>ppmv: 1 / 10 / 100 (dep. on meas. value)</td> </tr> <tr> <td>RH: 0.1</td> <td>mg/m^3: 1 / 10 / 100 (dep. on meas. value)</td> </tr> <tr> <td>$^{\circ}\text{C}_{td}$: 0.1</td> <td>$^{\circ}\text{F}$: 0.1</td> </tr> <tr> <td>$^{\circ}\text{F}_{td}$: 0.1</td> <td></td> </tr> <tr> <td>$^{\circ}\text{CtA}$: 0.1</td> <td></td> </tr> <tr> <td>$^{\circ}\text{FtA}$: 0.1</td> <td></td> </tr> </table>	$^{\circ}\text{C}$: 0.1	ppmv: 1 / 10 / 100 (dep. on meas. value)	RH: 0.1	mg/m^3 : 1 / 10 / 100 (dep. on meas. value)	$^{\circ}\text{C}_{td}$: 0.1	$^{\circ}\text{F}$: 0.1	$^{\circ}\text{F}_{td}$: 0.1		$^{\circ}\text{CtA}$: 0.1		$^{\circ}\text{FtA}$: 0.1	
$^{\circ}\text{C}$: 0.1	ppmv: 1 / 10 / 100 (dep. on meas. value)														
RH: 0.1	mg/m^3 : 1 / 10 / 100 (dep. on meas. value)														
$^{\circ}\text{C}_{td}$: 0.1	$^{\circ}\text{F}$: 0.1														
$^{\circ}\text{F}_{td}$: 0.1															
$^{\circ}\text{CtA}$: 0.1															
$^{\circ}\text{FtA}$: 0.1															
Normed atmospheric dewpoint		Rotatability (display positioning)	350° around housing axis												
Measuring range	-70 to $-15\text{ }^{\circ}\text{CtdA}$ (-112 to $-5\text{ }^{\circ}\text{FtdA}$) (at 30 bar rel./ 435 psi) -54 to $+10\text{ }^{\circ}\text{CtdA}$ (-94 to $+50\text{ }^{\circ}\text{FtdA}$) (at 3 bar rel./43.5 psi) -45 to $+30\text{ }^{\circ}\text{CtdA}$ (-76 to $+86\text{ }^{\circ}\text{FtdA}$) (at 0 bar rel./0 psi)	Installation													
Temperature		Thread / process connection	G $\frac{1}{2}$ thread (order code 01) or NPT $\frac{1}{2}$ " thread (order code A 02)												
Measuring range	0 to $50\text{ }^{\circ}\text{C}$ (32 to $+122\text{ }^{\circ}\text{F}$)	Miscellaneous													
Measurement uncertainty	$\pm 0.5\text{ K}$ (0 to $50\text{ }^{\circ}\text{C}/32$ to $122\text{ }^{\circ}\text{F}$)	Protection class	IP65 (with plug attached and wire connected)												
Sensor	NTC	EMC	According to guideline 89/336 EEC												
Inputs and outputs		Operating conditions													
Analog outputs		Operating temperature (housing)	-20 to $+70\text{ }^{\circ}\text{C}$ ($+4$ to $+158\text{ }^{\circ}\text{F}$)												
Current/accuracy	4 to 20 mA (2-wire) / $\pm 40\text{ }\mu\text{A}$	Storage temperature	-40 to $+80\text{ }^{\circ}\text{C}$ (-40 to $+176\text{ }^{\circ}\text{F}$)												
Measurement rate	2 s	Process pressure	max. 50 bar (725 psi)												
Resolution	12 bit														
load	10 V DC: max. 100 Ω , 30 V DC: 950 Ω														
Scaling	Freely scalable via display buttons														
Switch outputs (opt. alarm plug, 0554 3302)															
Contacts	2 closer contacts, pot.-free, max. 30V/0.05A														
Switch thresholds	Standard 6 $^{\circ}\text{C}_{td}/12\text{ }^{\circ}\text{C}_{td}$, freely progr. with display														
Supply															
Voltage supply	24 V AC/V DC (10 to 30 V DC permitted); with alarm plug (0554 3302) 20 to 28 V DC														
Current consumption	21 mA (without alarm plug) 65 mA (with alarm plug)														



Dewpoint transmitter to $-45\text{ }^{\circ}\text{C}_{\text{td}}$

Technical drawings




- ① Standard connection plug (4 to 20 mA – 2-wire)
- ② Switch contact plug: cable connection plug for supply/analog output (4 to 20 mA – 2-wire)

Dewpoint transmitter to $-45\text{ }^{\circ}\text{C}_{\text{td}}$



Connection plan

With standard plug (included in delivery 0555 674x):




Pin plug terminals


- 1: + (4 to 20 mA), Supply 12 to 30 VDC
- 2: - (4 to 20 mA)
- 3: Not used
- 4: Measurement earth (cable shield)

Standard plug

This version provides a 4 to 20 mA analog output in 2-wire technology.



With switch contact plug (0554 3302)



Pin plug terminals

- 1: I + (4 to 20 mA) (A)
- 2: I - (4 to 20 mA) (B)
- 3: (connected with relay board ex-works)
- ⊥: Connect shield

Current signal and supply 20 to 28 V DC


Relay board terminals

- 1: 20 to 28 V DC (A)
- 2: LS +
- 3: LS -
- 4: US +
- 5: US -
- 6: 0 V DC (B)

The supply connections must be galvanically connected, i. e. make connection (A) - (A) or (B) - (B)!

Switch contact plug (0554 3302)

4 to 20 mA, 2-wire as well as 2 potential-free switch contacts + 2 LED



Max. switching 0.5 A/30 V

Order data testo 6740

	Order no.
Basic instrument (incl. plug for analog signal output)	
testo 6741, G $\frac{1}{2}$ thread, without display	0555 6741
testo 6742, NPT $\frac{1}{2}$ thread, without display	0555 6742
testo 6743, G $\frac{1}{2}$ thread, with display	0555 6743
testo 6744, NPT $\frac{1}{2}$ thread, with display	0555 6744

K – TEST, s.r.o.
 Letná 40
 042 60 Košice
 Tel/fax.: 055 6253633, 6255159
 ktest@iol.sk, ktest@ktest.sk
 www.ktest.sk, www.testo.sk
 0905 522488