

testo 315-2

CO warning instrument

Use testo 315-2 to check the CO level in ambient air. Even low concentrations of the highly poisonous gas are detected. In this way, you can judge whether the burner flue gases are being fully drawn off.

- Reliable warning of CO poisoning
- DVGW approval
- Adjustment of different alarm limits
- Printout with date/time and recommended value (alarm limit)
- With calibration protocol
- TopSafe, protection case for tough applications
- Quick and practical documentation of data on location, printout with date/time and recommended value (alarm limit)

testo 315-2, CO warning instrument, with battery and calibration protocol

Part no.
0632 0317



Accessories	Part no.
Transport and Protection	
TopSafe (protection case), with bench stand Protects instrument from dirt and impact	0516 0443
Magnetic bench stand suitable for TopSafe 0516 0443 For positioning on boilers, for example	0554 0407
Multi-function clip (for instrument with TopSafe) consisting of multi-function clip and magnetic holder	0554 0398
Case For secure storage of measuring instrument	0516 0191
Transport case (plastic) For transport and secure storage of measuring instrument and accessories	0516 3120
Printer and Accessories	
Testo printer with cordless IRDA and infrared interface, 1 roll of thermal paper and 4 round cell batteries	0554 0547
Recharger for printer (with 4 standard rech. batteries) Rechargeable batteries are recharged externally	0554 0110
Spare thermal paper for printer (6 rolls)	0554 0569
Spare thermal paper for printer (6 rolls), permanent ink Measurement data documentation legible for up to 10 years	0554 0568
Additional Accessories and Spare Parts	
9V rech. battery for instrument Instead of battery	0515 0025
Recharger for 9V rechargeable battery For external recharging of 0515 0025 battery	0554 0025
CO flue gas probe to measure CO in flue gas, with exchangeable NOx filter and pressure reducer	0554 3154
Spare particle filter (10 off) For CO flue gas probe	0554 0040
Filter granulates (refill set) to renew NOx filter in CO flue gas probe	0554 3167
Calibration Certificates	
ISO calibration certificate/Flue gas Calibration points 2.5% O ₂ ; 100 and 1000 ppm CO; 800 ppm NO; 80 ppm NO ₂ ; 1000 ppm SO ₂	0520 0003
ISO calibration certificate/CO CO probes; calibration points 0; 80 ppm	0520 0039

Recommended set
testo 315-2, CO warning set
- CO warning instrument, with battery and calibration protocol (Part no. 0632 0317)
- TopSafe (protection case), with bench stand (Part no. 0516 0443)
- Case (Part no. 0516 0191)

Technical data	
Meas. range	0 to +2000 ppm CO
Accuracy	±10 ppm CO (0 to +100 ppm CO)
±1 digit	±10% of mv (+100 to +2000 ppm CO)
Resolution	1 ppm CO
Alarm limits	50/100/500 ppm
Zero point adjustment	Automatically when switched on
Oper. temp.	+5... +45 °C
Battery type	9V block battery
Dimensions	215 x 68 x 47 mm
Weight	400 g
Display	LCD, 2 lines
Material/Housing	ABS
Warranty	2 years