

The gas leak detector for a fast overview

testo 316-2

The testo 316-2 is extremely user-friendly and ideally suited to fast check measurements thanks to its integrated pump, its optical presentation of the gas concentrations detected, and the integrated rechargeable battery.

- Optical and audible alarm with bar display for increasing and dangerous gas concentrations
- Trend display shows maximum leakage

- Integrated pump
- Flexible measurement probe for inaccessible places
- Earphone connection for secure leakage localization in loud surroundings
- High duration of use thanks to rechargeable battery

testo 316-2

Electronic gas leak detector with flexible measurement probe, incl. mains charger and earphones

Part no. 0632 3162

Technical data

Meas. range	10 ppm to 4,0 Vol. % CH ₄ 10 ppm to 1,9 Vol. % C ₃ H ₈ 10 ppm to 4,0 Vol. % H ₂
1st alarm limit	200 ppm CH ₄ 100 ppm C ₃ H ₈ 200 ppm H ₂
2nd alarm limit	10.000 ppm CH ₄ 5.000 ppm C ₃ H ₈ 10.000 ppm H ₂
Battery life	6 h
Dimensions	190 x 57 x 42 mm



Accessories Ordering data

Earphones, black with ear cushions

Mains unit (output: 12V, DC, 300mA)

Part no.

0554 5001

0554 1093