

testo 206 pH1

Compact pH tester – For liquids

The pH measuring instrument for fast checks on liquids. The combination of pH immersion tip and temperature probe for fast and efficient temperature compensation is unique.

The Testo pH probe is leak-proof, maintenance-free, robust and not affected by dirt thanks to the large volume of gel electrolyte and the dual wall diaphragm.

- TopSafe: Robust, water-tight, hygienic and dishwasher-proof protection case (IP68)
- Maintenance-free gel electrolyte
- Automatic full-scale recognition
- Built-in temperature probe
- 1, 2 or 3 point calibration possible

testo 206-pH1 instrument set:
One-hand pH/°C measuring instrument, pH1 probe head for liquids, storage cap with gel, TopSafe and belt/wall holder

Part no.
0563 2061



pH1 probe head for liquids

Set	Part no.
testo 206-pH1 Starter Set: One-hand pH/°C measuring instrument, pH1 probe head for liquids, storage cap with gel, calibration dosing bottles 250 ml pH 4+7, TopSafe, belt/wall holder and aluminium case	0563 2061

Accessories	Part no.
Additional accessories and spare parts	
Spare pH probe for testo 206 incl. gel storage cap	0650 2061
Storage cap for testo 206 with KCl gel filling	0554 2067
Storage cap for testo 206 with KCl gel filling (pack of 3)	0554 2068
pH buffer solution 4.01 in dosing bottle (250 ml) with DKD calibration certificate	0554 2061
pH buffer solution 4.01 in dosing bottle (3 x 250 ml per pack) with DKD calibration certificate	0554 2062
pH buffer solution 7.00 in dosing bottle (250 ml) with DKD calibration certificate	0554 2063
pH buffer solution 7.00 in dosing bottle (3 x 250 ml per pack) with DKD calibration certificate	0554 2064
pH buffer solution 10.01 in dosing bottle (250 ml) with DKD calibration certificate	0554 2065
pH buffer solution 10.01 in dosing bottle (3 x 250 ml per pack) with DKD calibration certificate	0554 2066

Technical data	
Probe type	pH electrode / NTC
Meas. range	0 to 14 pH 0 to 60 °C (Short-term to +80 °C max. 5 min)
Accuracy	±0.02 pH ±0.4 °C
Resolution	0.01 pH 0.1 °C
Oper. temp.	0 to +60 °C
Storage temp.	-20 to +70 °C
No. meas. channels	2 channel
Temperature compensation	Automatic
Meas. rate	2 measurements per seconds
Battery type	1x CR2032
Material/Housing	ABS with TopSafe, Protection type IP 68
Battery life	80 h (Auto Off 10 min)
Dimensions	197 x 33 x 20 mm
Weight	69 g
Display	LCD, 2 lines