

Testo fast printer

The universal printer with infrared interface saves you time since it saves the print data prior to printing. Data transfer is completed within 2 seconds. The instrument is then immediately ready for operation.

The readings are saved black on white with date and time.

Testo fast printer with wireless infrared interface, 1 roll thermal paper and 4 AA batteries

Part no.
0554 0549

Universal infrared printer

- System compatibility with other Testo measuring instruments (also downward compatibility)
- Fast data transfer, the measuring instrument is ready for use again within 2 sec.
- Fast print function thanks to newest line printer
- Energy-saving Auto-off/Wake-up function
- Testo design with integrated magnetic plate
- Robust housing (adapted to testo 327)
- Mains operation possible (same mains unit as for testo 327/330)



Technical data

Printer type	infrared-controlled thermal printer, adjustable contrast, graphic-capable	Oper. temp.	0 to +50 °C
		Storage temp.	-40 to +60 °C
		Power supply	4 AA batteries 1.5 V (or rechargeables) Mains unit GV/1.2A
Reception radius	max. 2 m	Weight	430 g
Dimensions	147 x 77 x 47 mm		

Accessories

	Part no.
Spare thermal paper for printer (6 rolls)	0554 0569
Spare thermal paper for printer (6 rolls), permanent ink, measurement data documentation legible for up to 10 years	0554 0568
External fast charger for 1-4 AA rech. batteries, incl. 4 Ni-MH rech. batteries with individual cell charging and charge control display, incl. impulse trickle charging, integrated discharge function, with built-in international mains plug, 100-240 V, 300 mA, 50/60 Hz	0554 0610