

testo 610

testo 610 measures relative air moisture and temperature simultaneously.

Dew point calculation and wet bulb as well as Hold function and max./min. display are possible with this instrument.

testo 610; humidity and temperature measuring instrument incl. protective cap, batteries and calibration protocol

Part no.
0560 0610

Pocket size air moisture and air temperature measuring instrument

- Air moisture and air temperature
- Dewpoint calculation and wet bulb included
- Hold function and max./min. values
- Backlit display
- Long-term stable Testo humidity sensor
- Protective cap for safe storage
- Belt case, wrist strap and calibration protocol included



Technical data

Meas. range	0 to 100 %RH -10 to +50 °C
Accuracy ±1 digit	±2.5 %RH (5 to 95 %RH) ±0.5 °C
Resolution	0.1 %RH 0.1 °C
Measuring rate	1 s
Weight	90 g (batteries and protective cap included)

Oper. temp.	-10 to +50 °C
Storage temp.	-40 to +70 °C
Battery type	2 batteries Type AAA
Battery life	200 h (average, without display illumination)
Dimensions	119 x 46 x 25 mm (incl. protective cap)
Protection class	IP20

Accessories

	Part no.
ISO calibration certificate humidity Calibration points 11.3 %RH and 75.3 %RH at +25°C	0520 0006
ISO calibration certificate/temperature temp. data logger; calibration points -8°C; 0°C; +40°C per channel/instrument	0520 0171