

## testo 826-T1

testo 826-T1 for non-contact and quick temperature checks on food - packaging is not damaged. The adjustable alarm (flashing display) indicates immediately if a limit value has been exceeded.

testo 826-T1, Infrared thermometer without sighting, with TopSafe and wall/belt holder

Part no.  
**0563 8261**

## Food infrared thermometer

- Screening test - measurement, without damaging the packaging
- Small and practical
- Upper and lower limit value monitoring with optical alarm (flashing display)
- Included: TopSafe (IP67) protection case, robust and hygienic, dishwasher-safe
- TopSafe case protects the instrument from dust, dirt and water ingress
- Wall/belt holder included
- Water-proof and robust thanks to TopSafe (IP67)



Technical data			
Meas. range	-50 to +300 °C	Battery type	2 lithium batteries (CR2032)
Accuracy	±1.5 °C (-20 to +100 °C)	Battery life	Approx. 150 h
±1 digit	±2 °C or 2% of mv (remaining range)	Dimensions	148 x 34.4 x 19 mm
Resolution	0.5 °C	Display	LCD, 1 line
Oper. temp.	0 to +50 °C	Weight	80 g
Storage temp.	-40 to +70 °C	Warranty	2 years

Accessories	Part no.
ISO calibration certificate/Temperature, For air/immersion probes, calibration point -18°C	0520 0061
ISO calibration certificate/Temperature, For air/immersion probes, calibration point 0°C	0520 0062
ISO calibration certificate/Temperature, Infrared thermometers, calibration points -18°C, 0°C, +60°C	0520 0401