

## testo 826-T2

## Food infrared thermometer with laser sighting

In addition to the above advantages of testo 826-T1, testo 826-T2 has laser sighting and an audible alarm which signals when a fixed limit value has been exceeded.

**testo 826-T2, Infrared thermometer with laser sighting and audible alarm, incl. TopSafe and wall/belt holder**

Part no.

**0563 8262**

- Screening test - measurement, without damaging the packaging
- Small and practical
- Upper and lower limit value monitoring with optical alarm (flashing display)
- Included: TopSafe (IP67) protection case, robust and hygienic, dishwasher-safe
- TopSafe case protects the instrument from dust, dirt and water ingress
- Wall/belt holder included
- Water-proof and robust thanks to TopSafe (IP67)



### Technical data

|                      |  |
|----------------------|--|
| Meas. range          | -50 to +300 °C   |
| Accuracy<br>±1 digit | ±1.5 °C (-20 to +100 °C)<br>±2 °C or 2% of mv<br>(remaining range) |
| Resolution           | 0.5 °C   |
| Oper. temp.          | -20 to +50 °C  |

|               |                       |
|---------------|-----------------------|
| Storage temp. | -40 to +70 °C         |
| Battery type  | 2 AAA micro batteries |
| Battery life  | Approx. 20 h          |
| Dimensions    | 148 x 34.4 x 19 mm    |
| Display       | LCD, 1 line           |
| Weight        | 80 g                  |
| Warranty      | 2 years               |

### Accessories

|  | Part no.  |
|--|-----------|
| ISO calibration certificate/Temperature, For air/immersion probes, calibration point -18°C           | 0520 0061 |
| ISO calibration certificate/Temperature, For air/immersion probes, calibration point 0°C             | 0520 0062 |
| ISO calibration certificate/Temperature, For air/immersion probes, calibration points -18°C; 0°C     | 0520 0041 |
| ISO calibration certificate/Temperature, Infrared thermometers, calibration points -18°C, 0°C, +60°C | 0520 0401 |