

testo 826-T4

testo 826-T4 is the top model from the testo 826 series. In addition to the above-mentioned benefits of testo 826-T3, testo 826-T4 also has a laser sighting and a reliable audible alarm.

testo 826-T4, 2 in 1 thermometer with laser and alarm, TopSafe, wall/belt holder, protection cap and frozen food drill

Part no.

0563 8264

Infrared thermometer with penetration probe and laser sighting

- Penetration thermometer and non-contact infrared thermometer in one compact instrument
- Spot check with infrared side without damaging packaging
- Core temperature measurement with thin, robust measuring tip
- Upper and lower limit value monitoring with optical alarm (flashing display)
- TopSafe case protects instrument from dust, dirt, impact and water ingress



Technical data		
Probe type	Infrared	NTC
Meas. range	-50 to +300 °C	-50 to +230 °C
Accuracy ±1 digit	±1.5 °C (-20 to +100 °C) ±2 °C or 2% of mv (remaining range)	±0.5 °C (-20 to +99.9 °C) ±1 °C or 1% of mv (remaining range)
Resolution	0.5 °C	0.1 °C

Oper. temp.	-20 to +50 °C
Storage temp.	-40 to +70 °C
Battery type	2 AAA micro batteries
Battery life	Approx. 15 h

Display	LCD, 1 line
Weight	80 g
Dimensions	148 x 34.4 x 19 mm
Warranty	2 years

Accessories		Part no.
ISO calibration certificate/Temperature, For air/immersion probes, calibration point -18°C		0520 0061
ISO calibration certificate/Temperature, For air/immersion probes, calibration point 0°C		0520 0062
ISO calibration certificate/Temperature, For air/immersion probes, calibration points -18°C; +60°C		0520 0043
ISO calibration certificate/Temperature, For air/immersion probes, calibration points -18°C; 0°C; +60°C		0520 0001