

## testo 926

## Fast, Accurate All-Round Thermometer

The fast-action, efficient temperature measuring instrument, testo 926, for the food sector. The optional TopSafe protection case renders it insensitive to dirt, therefore making it the ideal partner for large-scale kitchens, hotels, restaurants or the food industry. Besides measuring minimum and maximum values, readings can also be printed on site on the Testo printer. In addition to the wide range of standard probes with cable, a wireless radio probe can be used simultaneously, if required.

- Fast-action probes for every application
- Wireless measurement with radio probes possible (optional)
- Measurement data printout on site on the Testo printer
- TopSafe, the indestructible protection case (optional)
- Minimum/maximum value memory
- Large backlit display
- Auto-Hold automatically recognises full-scale value
- Audible alarm (adjustable alarm limits)



testo 926-1, 1 channel food temperature measuring instrument  
T/C Type T, audible alarm, connection to an optional radio probe, with battery and calibration protocol

Part no.  
**0560 9261**

Air probes	Illustration	Meas. range	Accuracy	t <sub>99</sub>	Part no.
Robust, affordable air probe, T/C Type T	 Conn.: Fixed cable 1.2 m	-50 to +350 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range)	25 s	0603 1793
Surface probes	Illustration	Meas. range	Accuracy	t <sub>99</sub>	Part no.
Waterproof surface probe with widened measurement tip for flat surfaces, T/C Type T	 Conn.: Fixed cable 1.2 m	-50 to +350 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range)	30 s	0603 1993
Immers./penetr. probes	Illustration	Meas. range	Accuracy	t <sub>99</sub>	Part no.
Waterproof standard immersion/penetration probe, T/C Type T	 Conn.: Fixed cable	-50 to +350 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range)	7 s	0603 1293
Food probes	Illustration	Meas. range	Accuracy	t <sub>99</sub>	Part no.
Robust food penetration probe with special handle, reinforced cable (PUR), T/C Type T	 Conn.:	-50 to +350 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range) Class 1	6 s	0603 2492
Frozen food probe, corkscrew design, T/C Type T	 Conn.: Plug-in cable	-50 to +350 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range) Class 1	8 s	0603 3292
Stainless steel food probe (IP67) with PUR cable, T/C Type T	 Conn.: Fixed cable	-50 to +350 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range) Class 1	7 s	0603 2192
Waterproof precision immersion/penetration probe without visible penetration hole, T/C Type T	 Conn.: Fixed cable 1.2 m	-50 to +350 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range)		0603 2693
Stainless steel food probe (IP67), with Teflon cable to +250 °C, T/C Type T	 Conn.: Fixed cable	-50 to +350 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range) Class 1	7 s	0603 3392
Waterproof, super-quick needle probe for measurements without visible penetration hole, T/C Type T	 Conn.: Fixed cable	-50 to +250 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range)	2 s	0628 0027

✦ The measuring instrument inside TopSafe is waterproof with this probe.

**testo 926**
**Accessories / Technical data**

Food probes	Illustration	Meas. range	Accuracy	t <sub>99</sub>	Part no.
■ Robust penetration probe for food, measures frozen pieces such as pizza etc., Tmax handle and cable +70°C	<p>40 mm Ø 4 mm 25 mm Ø 2.5 mm Conn.: Fixed cable</p>	-50 to +250 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range) Class 1	5 s	0628 0028
■ Quick needle probe to monitor cooking in oven, T/C Type T	<p>60 mm Ø 1.4 mm Conn.: Fixed cable</p>	-50 to +250 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range) Class 1	2 s	0628 0030
Measurement tip with T/C adapter Type T, ideal for fast-action measurement on incoming goods	<p>Ø 1.5 mm 500 mm</p>	-50 to +350 °C	Class 1	5 s	0628 0023

■ The measuring instrument inside TopSafe is waterproof with this probe.

Accessories	Part no.
<b>Accessories for measuring instrument</b>	
9V rech. battery for instrument, instead of battery	0515 0025
Recharger for 9V rechargeable battery, for external recharging of 0515 0025 battery	0554 0025
<b>Printer and Accessories</b>	
Testo printer with wireless IRDA and infrared interface, 1 roll of thermal paper and 4 round cell batteries	0554 0547
Spare thermal paper for printer (6 rolls), measurement data documentation legible for up to 10 years	0554 0568
Spare thermal paper for printer (6 rolls)	0554 0569
External recharger incl. 4 Ni-MH rechargeable batteries with built-in, international mains adapter - 100-240 V, 300 mA, 50/60 Hz, 12 VA/instrument	0554 0610
<b>Transport and Protection</b>	
TopSafe, protects from impact and dirt	0516 0220
Transport case for measuring instrument, 3 probes and accessories	0516 0200
Transport case for measuring instrument and probes	0516 0201
Case for measuring instrument and probes	0516 0210
<b>Calibration certificates</b>	
ISO calibration certificate/Temperature For air/immersion probes, calibration points -18°C; 0°C; +60°C	0520 0001
ISO calibration certificate/Temperature Infrared thermometer; calibration points +60°C; +120°C; +180°C	0520 0002
ISO calibration certificate/Temperature meas. instr. with surface probe; calibration points +60°C; +120°C; +180°C	0520 0071
ISO calibration certificate/Temperature Single point calibration for surface thermometer; calibration point +60°C	0520 0072
ISO calibration certificate/Temperature Single point calibration for surface thermometer; calibration point +120°C	0520 0073
ISO calibration certificate/Temperature For air/immersion probes, calibration point -18°C	0520 0061
ISO calibration certificate/Temperature For air/immersion probes, calibration point 0°C	0520 0062
ISO calibration certificate/Temperature For air/immersion probes, calibration point +60°C	0520 0063
ISO calibration certificate/Temperature For air/immersion probes, calibration points -8°C; 0°C; +40°C	0520 0181

Technical data	
Probe type	Type T (Cu-CuNi) or NTC if radio immersion/penetration probes are used
Meas. range	-50 to +400 °C
Accuracy ±1 digit	±0.3 °C (-20 to +70 °C) ±(0.7 °C ±0.5% of mv) (remaining range)
Resolution	0.1 °C (-50 to +199.9 °C) 1 °C (remaining range)
Oper. temp.	-20 to +50 °C
Storage temp.	-40 to +70 °C
Battery type	9V block battery, 6F22
Battery life	200 h (connected probe, backlight off) 45 h (radio mode, backlight off) 68 h (connected probe, backlight always on) 33 h (radio mode, backlight always on)
Dimensions	182 x 64 x 40 mm
Material/Housing	ABS
Weight	171 g
Warranty	2 years

See back flap for radio probes